



- PORCELAIN
TILES
- MARBLE
- STONE
- AGGLOMERATES
- GRANITE
- ANTIQUE
EFFECT MARBLE
- COBBLE AND
RIVER STONES

Fila MP/90

Stainproofing agent for natural stone and polished porcelain tiles

What it's for

Fila MP/90 is a special impregnating liquid for various purposes:

For the protection of polished porcelain tiles: for easier removal of routine and stubborn dirt.

As a protective basecoat, to be followed by a suitable wax, for high-absorbency and unpolished natural stone pavings (e.g. "pietra serena", "peperino", etc.).

As stainproofing agent for polished natural stone surfaces (e.g. marble and granite). It is especially recommended on tables, kitchen worktops, window-sills and floors at risk of staining.

As a protection against graffiti and posters on walls with stone finishes, and for easier graffiti removal.



How it's used

Dilution: do not dilute. Ready to use.

Application:

For protection of polished porcelain tile floors and polished natural stone surfaces: apply a light, even, continuous coat of Fila MP/90 with a flat brush. After 24 hours, when the floor is dry, remove the excess from the surface with a single-disc professional polisher fitted with a white or beige disc, or a household polisher fitted with felt pads (or a dry cloth). Any stubborn residues due to over-application can be removed with a cloth dipped in Filasolv; this allows the excess to be re-spread and removed simultaneously, so the floor is ready for use at once.



For protecting unpolished natural stone pavings: check that the surface for protection is dry and absorbent. Brush on a coat of Fila MP/90. After 24 hours, when the floor is dry, complete the treatment with Stonewax or Filalonglife. Caution: when Fila MP/90 is used to protect unpolished natural stone pavings, the product should first be tested on a small portion of the surface to check for any changes in colour.



Containers

5 litre canisters in cartons of 4
1 litre canisters in cartons of 12
250 ml canisters in cartons of 12.

Composition

Blend of silicone compounds dispersed in de-aromatised hydrocarbon solvent.

Precautions

Ventilate the premises thoroughly during use and while the product is



Labelling

Symbols: St Andrew's Cross (N)

Risk warnings: inflammable product. Noxious; may cause lung damage if swallowed.

Safety warnings: do not inhale vapours. Avoid contact with the skin. If swallowed, do not stimulate vomiting; consult a doctor immediately, showing him the container or label. Contains: de-aromatised mineral turpentine.

Quantity

For polished porcelain tiles and polished stone: 2-3 litres for 100 m².
For natural stone: from 5 to 10 litres for 100 m² depending on the type of material.

Technical characteristics

Appearance: transparent liquid
Colour: colourless
O dour: slight odour of solvent
Density: 0.775 kg/litre
Flash point: 40°C